

CELENO

Nitrogen Gas Generator for GC x GC

Reference : CELENO.[Flow rate]/0 (Without compressor)
CELENO.[Flow rate]/1 (With compressor)



Description

With 20 L/min, the CELENO Nitrogen range provides a High Purity Nitrogen solution for GC x GC instrument with Cryogen. The generator has very low dew point to work with cryogenic applications without any freezing.

The CELENO is available without or with integrated oil free air compressor using the **Energy Saving Technology mode (EST)**. It is extremely compact and quiet in operation.

The generator is controlled using the latest in color touch screen technology to display the process in real time, inlet / outlet pressure, N2 Flow and status of the system with remote access for diagnostic control.

Utilizing **Advanced technology PSA** of separating Nitrogen and Oxygen to produce high quality Nitrogen gas on demand 24/7.



UNIQUE AND INTELLIGENT OPERATOR INTERFACE WITH REMOTE ACCESS

Applications

GC x GC with Cryogen

Benefits & Savings

INCREASED LABORATORY EFFICIENCY

A constant, uninterrupted gas supply of guaranteed purity eliminates interruptions of analyses to change cylinders and reduces the amount of instrument re-calibrations required.

IMPROVED ECONOMY

Pure nitrogen gas produced as standard.

IMPROVED SAFETY

Nitrogen produced at low pressure and ambient temperature removes the need for high pressure cylinders.

SECURITY OF SUPPLY

Integral oil free air compressor as an option guarantees continuous gas supply, independent of in house compressed air supply.

SIMPLE INSTALLATION

Gas generators can be installed in the laboratory, on or under a bench, eliminating the need for long gas lines from cylinders secured elsewhere.

Standard Features

- Intelligent color touch screen to provide simple and user friendly management of all functions of the unit
- Fully regenerative PSA technology
- Without or with integral oil free air compressor
- Quiet thanks to the Soundproofed compressor box and anti-vibration features
- Low N2 dewpoint < -60°C (< -76°F)
- Auto start
- Fast start-up purity < 60 min
- Audible alarm display and Visual maintenance indication with history log
- Outlet flow indicator
- Energy Saving Technology (EST):
 - Switch off the compressor when gas supply is not required
 - Allowing low energy consumption and increasing durability of the compressor
- Remote PC monitoring and diagnostic analysis via USB to interface the unit with customer's PC software (allow to carry out checks and maintenance effectively, only via a remote connection)
- Compact design
- Fit with wheels

N2

MODELS	CELENO.20	
Compressor	0 (Without)	1 (With)
GENERALS INFORMATIONS		
Max Nitrogen Flow rate	20 L/min	
Max Nitrogen pressure	6 bar (87 psi)	
Nitrogen purity	> 99.5% (< 0.5% O2)	
Nitrogen dewpoint	< -60°C (< -76°F)	
Particles	0.01 μ	
Inlet Air flow required @ 8 bar (116 psi) max	70 L/min	N/A
Min Inlet Air quality	ISO8573 - 1:2010 1.4.1	N/A
Touch screen	Touch screen (operating parameters, system status, alarms and maintenance)	
Max Relative Humidity	80% RH @ 25°C (77°F)	
Temperature range	From 5 - 25°C (41 - 77°F)	
Max Altitude	3000 Meters	
Noise level @ 1M	25 dB (A)	52 dB (A)
Dimensions (W x H x D)	47.5 x 66.2 x 79 cm (18.7" x 26" x 31")	
Weight (kg/lbs)	91 / 200	118 / 260
Power consumption	150 VA	850 VA
Electrical supply	220 - 240 V ac / 1 ph / 50 - 60 Hz	
	110 - 120 V ac / 1 ph / 50 - 60 Hz	
Fuse	10A	
CONNECTIONS		
Nitrogen outlet	G 1/4" (BSP) Female	
Air Inlet	G 1/4" (BSP) Female	N/A
COMMUNICATION		
USB/PC Control	In series	

Gold Service
 — Satisfaction Guaranteed —

The products are guaranteed 24 months*. Beyond, your investment continues to be supported by our maintenance program **[Gold Service]**. Our world class technical assistance offers Programmed preventive maintenance to ensure optimal performance of your Gas generator F-DGSI and a priority intervention in case of failure.

*Year 2 of warranty subject to generator being serviced at end of the first year by a F-DGSI-approved agent in accordance with fixed annual maintenance schedule. For full terms and conditions, visit www.f-dgs.com

F-DGSI France
 8, 10 rue du Bois Sauvage, bat Q18 - 91000 Evry France
 Tel. : +33(0)1 64 98 21 00
 Fax. : +33(0)1 64 98 00 43

Email : info@f-dgs.com
 Web : www.f-dgs.com

Certified Product

